



Pistol Grip Conversion Overview

Saiga 223, 5.45x39 & 7.62x39 Rifles

The pistol grip conversion is a pretty simple task, anybody who can wield a dremel and drill will have no problems with the conversion.

The Saiga small rifles will need 5 US made parts when adding a pistol grip. This is covered by the Fire Control Group (+3), Pistol Grip (+1) and Buttstock (+1)

You need:

- #1 - FCGPGC1, FCGPGC1SS or FCGPGC1DS - Fire Control Group.
- #2 - CONVKIT - Includes pistol grip nut & screw, allen wrench, drills & hole plugs.
- #3 - TGRAM - Triggerguard & hardware
- #4 - Pistol Grip
- #5 - Buttstock - Any stamped receiver AK buttstock will work

Drill the 2 rear FCG pin/rivet heads with the 3/16" drill bit (in the conversion kit) and punch them out the LH side of the receiver.

Remove the 2 front FCG retaining pins by clipping or prying the retaining wire out of the grooves in the pins and push the pins out the LH side of the receiver.

Remove all FCG parts, safety lever and buttstock. (rotate safety lever up straight vertical and pull out)

Remove the bottom receiver plate/triggerguard assembly by grinding the rivet heads attaching it to the receiver. (you do not need to remove the triggerguard from the receiver plate) Drill through the rivets and pop them out with a punch or nail or drill shank.

Touchup paint the bottom of the receiver. Duplicolor Ceramic Engine Enamel Low Gloss Black is a perfect match and dries quickly. Available at most automotive stores.

Assemble with new parts.